



DSP1
 0-2V FSD
 4 1/2 digit indicator
 See Circuit del20003.pdf in Analog Section or Buy
 a DPM from market. Auto Range Not Required.

use 74HCT40XX chips in place of CD40XX for only 5V and high speed designs. Use Shrink sleeves and proper gauge of wire.
 put 104 CD cap for all ICs from positive to negative close to IC, even if omitted in circuit, for opamps on dual supply two caps.
 unused inputs of logic and opamps pull up or down to avoid oscillations and noise. connect supply of all chips if not mentioned.
 "analog ground" and "digital ground" must be linked at power supply only, avoid loops, let grounds radiate from a ground plane.
 use MFR 1% for all Resistors, 33E means 33 ohms, 22K means 22 kilo ohms, 1M is 1 megohm. 10T tp means ten turn trimpot.
 '474 CD' is 47 with 4 zeros pF, 470000 pF, 470 nF, 0.47uF, ceramic disc. "pl" is plastic, low leakage multilayer.

delabs
 delabs design
delabs-circuits.com
delabs.net

Earlier This Circuit was ST02_1.pdf

delabs circuits and technologies		
Millivolt Source		
Size B	Document Number	Rev 1
	del30001	
Date:	Wednesday, March 09, 2005	Sheet 1 of 1